

*Northeast Sled Services LLC*  
*2016 4x4 Enhanced Diesel / 8500lbs*

**General Diesel truck specifications explained:**

**May not** pull in more than 2 classes unless announced the day of the pull.  
May pull in 3.0 class, but not workstock class.

**Engine Specs:**

- 1) 6 and 8 cylinders permitted.
- 2) Single turbo charger only – 2.6” inlet maximum on turbo.
- 3) Twin turbos stock only on 2008 or newer – factory mass equipped.
- 4) Non factory style air intake **before** turbo permitted.
- 5) No nitrous oxide, propane, or methanol injection permitted.
- 6) Water injection ok.
- 7) Air charge coolers allowed (ice, etc.)
- 8) Portable tuners (bully dog, etc.) are allowed.
- 9) Laptop computers are **not allowed**.

**Other Specs:**

- 1) Must have at least a 2 inch air gap between suspension and (bump stops) frame.  
Air bags ok as long as onboard air compressor or air storage tank is disabled.
- 2) Traction bars permitted.
- 3) Overhung or exposed weight permitted!
- 4) No weight in cab, all weight must be secured.
- 5) DOT approved tires only.
- 6) Dual rear tires permitted.
- 7) Must have driveline shielding same as 3.0 class.

**Hitch Specs:**

- 1) Hitch height must not exceed more than 26” high – must be a stock receiver – fixed hitch allowed – absolutely no trailer balls. Hitch insert must be solid (no hollow tube type).
- 2) **Minimum hitch hole size of 3” and must be easily accessible**. A hole smaller than 3” will not accept the hook on the sled.

**Safety Specs:**

- 1) Must wear helmet and seatbelts.
- 2) 2lb “ABC” dry chemical Fire extinguisher required.
- 3) Mud flaps required.

**Also -All General Safety Rules Apply!**

**Violation of any rule will be a disqualification for the event in which  
the violation occurs – no points no money!**