

*Northeast Sled Services LLC*  
**2016 2WD SUPERSTOCK / 5000lbs and 5200lbs RULES**

**Engine Specs:**

- 1) Limited to one engine only. \*No big blocks for 2016\*
- 2) Gas only - **No nitrous oxide or methanol or compressed air\*\*** Race fuel allowed.
- 3) No blowers or turbos.
- 4) Engine limited to 410 cubic inch.
- 5) Must be dual plane intake with maximum 2" spacer or adaptor plate allowed. .
- 6) Limited to one carburetor
- 7) Exhaust must be straight upright or straight back under truck.

**Other Specs:**

- 1) Rear suspension not required.
- 2) Rear axle must be a dana 80, or corporate 14 bolt or smaller. **No Rockwells**
- 3) Chassis must not exceed 15 feet of wheelbase from center of rear axle to forward most point of truck, including weights and brackets.
- 4) Chassis must be mass produced factory built 1 ton or less frame – must be OEM frame – no tube or boxed frames.
- 5) Single gear box only can be manual or automatic. High stall torque converters allowed. No transfer cases or 2 speed rears allowed.
- 6) 34X18 Maximum tire size allowed (puller tires and dot allowed) - No dual wheels.
- 7) Double cut tires not allowed.
- 8) **No weights** allowed in cab.

**Hitch Specs:**

- 1) Hitch must not exceed more than 45" back from center of rear housing
- 2) No more than 30" high
- 3) Minimum hole size of 3" and must be easily accessible.

**Safety Specs:**

- 1) Wheelie bars to be made to be minimum 10 inches behind rear tire and max 10 inches off the ground, to facilitate easier hooking and a more rigid wheelie bar - \*bump stops highly recommended\*
- 2) Universal joints must be shielded with a minimum 1/4" thick by 6" wide steel straps enclosed 360 degrees – also minimum of one loop per drive shaft.
- 3) All transmissions and clutches will be covered with 1/8" steel scatter shield, blanket, or equivalent material – this includes top and sides completely covered.
- 4) All fans must be shielded 360 degrees with minimum of 1/8" steel.
- 5) Side shield on engines of 1/8" minimum – at least covering the spark plugs.
- 6) Driver must wear a DOT approved helmet – seat belts required and must be worn.
- 7) Minimum of 2lb fire extinguisher must be loaded and in the vehicle.
- 8) **KILL SWITCHES MADATORY** – Kill switch must be of the tether type and placed in the center, in an un-obstructed area on the rear of the vehicle.
- 9) Neutral switches mandatory.
- 10) Must have at least a 4 point roll cage on open cabs (T buckets etc.), and at least a 2 point internal roll cage on trucks with enclosed cabs.

**\*\* Serious Safety Offence – One year and ten (10) day disqualification.**

**Also -All General Safety Rules Apply!**

**Violation of any rule will be a disqualification for the event in which  
the violation occurs – no points no money!**